



© NXP SEMICONDUCTORS N.V. ALL RIGHTS RESERVED	MECHANICAL OUTLINE	PRINT VERSION NOT TO SCALE
TITLE: FCPBGA WITH LID, 35 X 35 PKG X 2.67 PKG, 1.0 MM PITCH, 1152 I/O	DOCUMENT NO: 98ASA00464D	REV: D
	STANDARD: NON-JEDEC	
	SOT1650-1	12 JAN 2016



NOTES:

1. ALL DIMENSIONS IN MILLIMETERS.

2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.

3. MAXIMUM SOLDER BALL DIAMETER MEASURED PARALLEL TO DATUM A.

4. DATUM A, THE SEATING PLANE, IS DETERMINED BY THE SPHERICAL CROWNS OF THE SOLDER BALLS.

5. PARALLELISM MEASUREMENT SHALL EXCLUDE ANY EFFECT OF MARK ON TOP SURFACE OF PACKAGE.

6. ALL DIMENSIONS ARE SYMMETRIC ACROSS THE PACKAGE CENTER LINES, UNLESS DIMENSIONED OTHERWISE.

7. 35.2MM MAXIMUM PACKAGE ASSEMBLY (LID + LAMINATE) X AND Y.

8. PIN 1 THRU HOLE IS CENTERED ON THE FOOT.

© NXP SEMICONDUCTORS N.V. ALL RIGHTS RESERVED	MECHANICAL OUTLINE	PRINT VERSION NOT TO SCALE	
TITLE: FCPBGA WITH LID, 35 X 35 PKG X 2.67 PKG, 1.0 MM PITCH, 1152 I/O		DOCUMENT NO: 98ASA00464D	REV: D
		STANDARD: NON-JEDEC	
		SOT1650-1	12 JAN 2016